



MIPOLAM TROPLAN PLUS

DESCRIPTION

Total thickness	EN 428	mm	2.00
Weight	EN 430	g/m ²	3135
Width of sheet	EN 426	cm	200
Length of sheet	EN 426	lm	20
Tile size	EN 427	mm	
Number of tiles per package	-	-	

CLASSIFICATION

Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
K rating	-	class	K5
Fire rating	EN 13 501-1	class	B _{fl} -s1
Critical radiant flux	ASTM E648	W/cm ²	
Marine Equipment Directive International Maritime Organisation	Directive 96/98/EC I.M.O code F.T.P.	n°	
Static electrical propensity	EN 1815	kV	2

PERFORMANCE

Wear resistance	EN 660.1	mm	≤ 0.15
Wear Group	EN 649	group	P
Dimensional stability	EN 434	%	≤ 0.4
Residual indentation	EN 433	mm	0.03
Thermal conductivity	EN 12 524	W/(m.K)	
Colour fastness	EN ISO 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	class	OK
Anti-bacterial and fungicidal treatment	-	-	OK
Surface treatment	-	-	PUR